

TC-L Slim Line 36W




Technical data

Light distribution	large-area illumination, reflectors
Control gear	electronic ballast - flicker-free light
Mains lead	approx. 2m cable H03VV-F3G0,75 with Schuko-plug, 220-240V~/50-60Hz
Fluorescent lamp	equipped with a single 36W TC-L compact fluorescent lamp
Switch	switch in articulated arm (ON/OFF)
Power	36W
Protection class	IP20
Joint arm	smooth-action floating arm, spring-supported center and base joints
Weight	approx. 2,8kg

Profile

- Well-shaped, made from high quality aluminum
- Ball joint; freely positionable sleek reflector head, swiveling, rotating and inclining
- Smooth-action floating arm, spring-supported center and base joints
- Dimensions: **445 x 90 x 45 mm**
- Colour: silver-gray painting RAL 9006



Light properties

Illuminance at the working area:

Measuring distance

40cm

Lux

up to 3200

- Powerful, large-area light - equipped with a single 36W TC-L compact fluorescent lamp
- Very high colour rendition - **CRI > 90**, colour temperature **5400 K** (daylight white)
- Balanced luminance distribution
- **Optional dimmable** (1 - 100%)
- Optional glare protection or metal raster
- Electronic ballast - flicker-free light

Mounting brackets

- Picture 1: screwdown flange 60 x 60 mm **(incl.)**
- Picture 2: table clamps with a span of 0-44mm or 15-85mm
- Picture 3: wall angle
- Picture 4: table base 10,5kg, 240 x 265 mm



picture 1



picture 2



picture 2



picture 3



picture 4